



**QMFZ2.E80533
Plastics - Component**

For enhanced search functionality, please visit UL's iQ™ Family of Databases.

Click on a product designation for complete information.

[Page Bottom](#)

Plastics - Component

[See General Information for Plastics - Component](#)

MAR-BAL INC
16930 MUNN RD
CHAGRIN FALLS, OH 44023-5411 USA

E80533

Material Dsg	Color	Min. Thk mm	Flame Class	H		RTI		H	D		
				W	A	Elec	Mech	V	4	C	
				I	I	Imp	Str	T	9	T	
Unsaturated Polyester (UP), glass reinforced, furnished as bulk.											
MB1000-15	ALL	1.5	HB	1	0	130	130	130	0	4	1
		3.0	-	-	-	130	130	130			
MB2000-10	ALL	1.5	V-0	0	0	130	130	130	0	3	1
		3.0	-	-	-	130	130	130			
MB2000-10AH	ALL	1.5	V-0	0	0	130	130	130	0	4	0
		3.0	V-0	0	0	130	130	130			
MB2000-10CG	VT	1.7	V-0	-	-	130	130	130	-	-	-
		3.0	V-0	-	-	130	130	130			
MB2000-10DB	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	-	-	-	130	130	130			
		6.0	-	-	-	130	130	130			
MB2000-10DW	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	-	-	-	130	130	130			
		6.0	-	-	-	130	130	130			
MB2000-10PS	ALL	1.5	V-0	0	0	130	130	130	0	3	0
		3.0	-	0	0	130	130	130			
MB2000-10TG	WT	1.5	V-0	-	-	130	130	130	-	-	-
		3.0	-	-	-	130	130	130			
MB2000-15, MB2000-15-AR											
	ALL	1.5	V-0	0	0	130	130	130	0	3	0
		3.0	-	-	-	130	130	130			
MB2000-15LS	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	V-0	0	0	130	130	130			
MB2000-15SF	ALL	1.5	V-0	1	0	130	130	130	0	4	0

		3.0	V-0	0	0	130	130	130			
MB2000-20	ALL	1.5	V-0	0	0	130	130	130	0	3	0
		3.0	V-0	0	0	130	130	130			
MB2000-20A	ALL	1.5	V-1	1	0	130	130	130	0	4	0
		3.0	-	-	-	130	130	130			
MB2000-25	ALL	1.5	V-0	0	0	130	130	130	0	2	1
		3.0	-	-	-	130	130	130			
MB2000-25EK	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	V-0	0	0	130	130	130			
MB2000-5	ALL	1.5	V-0	0	0	130	130	130	0	3	1
		3.0	-	-	-	130	130	130			
MB3000-15	ALL	2.3	V-0	-	-	105	130	130	-	-	-
MB4000@	ALL	1.65	V-0, 5VA	1	0	130	130	130	0	3	0
		1.65	RP15	-	-	130	130	130			
		3.0	V-0,5VA	0	0	130	130	130			
		3.0	RP15	-	-	130	130	130			
MB5500	ALL	1.3	V-0	0	0	160	160	170	0	4	0
		2.3	V-0, 5VA	0	0	160	160	170			
		3.0	V-0, 5VA	-	-	160	160	170			
MB9000-20	ALL	1.5	V-0	0	0	130	130	130	0	4	0
		3.0	V-0	-	-	130	130	130			
Unsaturated Polyester (UP), furnished as bulk.											
MB-1000-PC	BK	1.5	HB	0	0	130	130	130	-	-	2
		3.0	HB	0	0	130	130	130			
MB-3000-15-NY	ALL	1.5	V-0, 5VA	0	0	130	130	130	0	4	0
		3.0	V-0, 5VA	0	0	130	130	130			
MB-3000-20-NY	ALL	1.5	V-0, 5VA	0	0	130	130	130	0	4	0
		3.0	V-0, 5VA	0	0	130	130	130			

@ - Material has been subjected to inclined plane tracking test in accordance with ASTM D-2303, tracking less than 1 inch after 1500 minutes at 2500 volts.

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2014-01-24

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission

from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".
