



**QMFZ8.E80533  
Plastics Certified for Canada - Component**

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

**Plastics Certified for Canada - Component**

[See General Information for Plastics Certified for Canada - Component](#)

**MAR-BAL INC**

E80533

16930 MUNN RD

CHAGRIN FALLS, OH 44023-5411 USA

		Min.		H	H	H	RTI			C
		Thk	Flame	W	A	V	Elec	Mech		T
Mtl Dsg	Color	mm	Class	I	I	A		Imp	Str	I
<b>Unsaturated Polyester (UP), glass reinforced, furnished as bulk.</b>										
<b>MB1000-15</b>	ALL	1.5	-	1	0	1	130	130	130	1
		3.0	-	-	-	-	130	130	130	
<b>MB2000-10</b>	ALL	1.5	V-0	0	0	1	130	130	130	1
		3.0	-	-	-	-	130	130	130	
<b>MB2000-10AH</b>	ALL	1.5	V-0	0	0	0	130	130	130	0
		3.0	V-0	0	0	0	130	130	130	
<b>MB2000-10CG</b>	VT	1.7	V-0	-	-	-	130	130	130	-
		3.0	V-0	-	-	-	130	130	130	
<b>MB2000-10DB</b>	ALL	1.5	V-0	1	0	0	130	130	130	0
		3.0	-	-	-	-	130	130	130	
		6.0	-	-	-	-	130	130	130	
<b>MB2000-10DW</b>	ALL	1.5	V-0	1	0	0	130	130	130	0
		3.0	-	-	-	-	130	130	130	
		6.0	-	-	-	-	130	130	130	
<b>MB2000-10PS</b>	ALL	1.5	V-0	0	0	0	130	130	130	0
		3.0	-	0	0	0	130	130	130	
<b>MB2000-10TG</b>	WT	1.5	V-0	-	-	-	130	130	130	-
		3.0	-	-	-	-	130	130	130	
<b>MB2000-15, MB2000-15-AR</b>										
	ALL	1.5	V-0	0	0	1	130	130	130	0
		3.0	-	-	-	-	130	130	130	
<b>MB2000-15LS</b>	ALL	1.5	V-0	1	0	0	130	130	130	0
		3.0	V-0	0	0	0	130	130	130	
<b>MB2000-15SF</b>	ALL	1.5	V-0	1	0	0	130	130	130	0
		3.0	V-0	0	0	0	130	130	130	

<b>MB2000-20</b>	ALL	1.5	V-0	0	0	0	130	130	130	0
		3.0	V-0	0	0	0	130	130	130	
<b>MB2000-20A</b>	ALL	1.5	V-1	1	0	-	130	130	130	0
		3.0	-	-	-	-	130	130	130	
<b>MB2000-25</b>	ALL	1.5	V-0	0	0	1	130	130	130	1
		3.0	-	-	-	-	130	130	130	
<b>MB2000-25EK</b>	ALL	1.5	V-0	1	0	0	130	130	130	0
		3.0	V-0	0	0	0	130	130	130	
<b>MB2000-5</b>	ALL	1.5	V-0	0	0	1	130	130	130	1
		3.0	-	-	-	-	130	130	130	
<b>MB3000-15</b>	ALL	2.3	V-0	-	-	-	105	130	130	-
<b>MB4000@</b>	ALL	1.65	V-0, 5VA	1	0	3	130	130	130	0
		1.65	RP15	-	-	-	130	130	130	
		3.0	V-0,5VA	0	0	3	130	130	130	
		3.0	RP15	-	-	-	130	130	130	
<b>MB5500</b>	ALL	1.3	V-0	0	0	0	160	160	170	0
		2.3	V-0, 5VA	0	0	0	160	160	170	
		3.0	V-0, 5VA	-	-	-	160	160	170	
<b>MB9000-20</b>	ALL	1.5	V-0	0	0	0	130	130	130	0
		3.0	V-0	-	-	0	130	130	130	
<b>Unsaturated Polyester (UP), furnished as bulk.</b>										
<b>MB-1000-PC</b>	BK	1.5	-	0	0	-	130	130	130	2
		3.0	HB	0	0	-	130	130	130	
<b>MB-3000-15-NY</b>	ALL	1.5	V-0, 5VA	0	0	-	130	130	130	0
		3.0	V-0, 5VA	0	0	-	130	130	130	
<b>MB-3000-20-NY</b>	ALL	1.5	V-0, 5VA	0	0	-	130	130	130	0
		3.0	V-0, 5VA	0	0	-	130	130	130	

@ - Material has been subjected to inclined plane tracking test in accordance with ASTM D-2303, tracking less than 1 inch after 1500 minutes at 2500 volts.

Marking: Company name and material designation, generic polymer identification, color number where appropriate and batch or lot number or date of manufacture on container, wrapper or molded on finished part.

Last Updated on 2014-01-24

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following

format: "© 2014 UL LLC".