



TENSILE STRENGTH:.....2000 LBS
 CANTILEVER STRENGTH:1,500 LBS
 COMPRESSIVE STRENGTH:.....20,000 LBS
 TORQUE STRENGTH: 25 FT. LBS
 ARC RESISTANCE:.....180 SEC
 UL 94 FLAME RESISTANCE:94 V-0
 CREEP DISTANCE: 1 - 5/8"
 TRACK RESISTANCE:.....600 MINUTES

1603-2D Option
 TENSILE STRENGTH:.....2500 LBS
 CANTILEVER STRENGTH:1,800 LBS
 TORQUE STRENGTH: 30 FT. LBS

PART NUMBER	INSERT SIZE	MATERIAL
1603-2A	3/8 - 16	Aluminum
1603-2D	3/8 - 16	Aluminum
1603-408	M8 x 1.25	Brass
1603-410	M10 x 1.5	Brass

CONFIDENTIAL
 This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.
 DATE:



MAR-BAL, Incorporated
 5400 Reserve Way
 Dublin, VA 24084
 www.mar-bal.com

TITLE GLASTIC SERIES STANDOFF INSULATORS	
PART NUMBER: 1603-XX	SUGGESTED INDOOR RATING: 600 V
SHEET 1 OF 1	SCALE 1.000