



TENSILE STRENGTH:.....2000 LBS  
 CANTILEVER STRENGTH: .....1,750 LBS  
 COMPRESSIVE STRENGTH:.....20,000 LBS  
 TORQUE STRENGTH: ..... 40 FT. LBS  
 ARC RESISTANCE:.....180 SEC  
 UL 94 FLAME RESISTANCE: .....94 V-0  
 CREEP DISTANCE: .....1/4" + DIM "A"  
 TRACK RESISTANCE:.....600 MINUTES

HEIGHT "A"	THREADS	PART NUMBER	"B" (reference)	VOLTAGE
1.50 [38.1]	1/4 - 20	2015-1A	3/16"	1500
	5/16 - 18	2015-2A	3/16"	1500
	3/8 - 16	2015-3A	3/16"	1500
1.75 [44.5]	5/16 - 18	2015-2B	7/16"	2000
	3/8 - 16	2015-3B	7/16"	2000
2.00 [50.8]	5/16 - 18	2015-2C	11/16"	2300
	3/8 - 16	2015-3C	11/16"	2300
	1/2 - 13	2015-4C	11/16"	2300
2.25 [57.2]	3/8 - 16	2015-3D	15/16"	2700
	1/2 - 13	2015-4D	15/16"	2700

**CONFIDENTIAL**  
 This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.



**MAR-BAL, Incorporated**  
 5400 Reserve Way  
 Dublin, VA 24084  
 www.mar-bal.com

TITLE <b>GLASTIC SERIES INSULATORS</b>	
PART NUMBER:	SUGGESTED INDOOR RATING:
2015-XX	SEE CHART
DATE:	SCALE 1.000

DATE:

SHEET 1 OF 1

SCALE 1.000