



OVER SURFACE SPACING
(CREEP DISTANCE) = 1.938"

AVAILABLE THREADS

UNC THREAD STYLES

PART NUMBER	INSERT SIZE	MATERIAL
4150-S2	1/4-20 X 7/16	STEEL
4150-A3	5/16-18 X 3/8	ALUMINUM
4150-S3	5/16-18 X 3/8	STEEL
4150-A4	3/8-16 X 3/8	ALUMINUM
4150-S4	3/8-16 X 3/8	STEEL

METRIC THREAD STYLES

4150-S2/M6	M6 X 1.00 X 11.1	STEEL
4150-A3/M8	M8 X 1.25 X 9.5	ALUMINUM
4150-S3/M8	M8 X 1.25 X 9.5	STEEL
4150-A4/M10	M10 X 1.50 X 9.5	ALUMINUM
4150-S4/M10	M10 X 1.50 X 9.5	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 06-AUG-2008



MAR-BAL, Incorporated
5400 Reserve Way
Dublin, VA 24084
www.mar-bal.com

TITLE 4000 SERIES OCTAGON INSULATOR	
PART NUMBER: 4150-XX	SUGGESTED INDOOR RATING: 1.5 kV
SHEET 1 OF 1	SCALE 1.000