



OVER SURFACE SPACING  
(CREEP DISTANCE) = 2.438"

**AVAILABLE THREADS**

**UNC THREAD STYLES**

| PART NUMBER | INSERT SIZE   | MATERIAL |
|-------------|---------------|----------|
| 4200-A3     | 5/16-18 X 3/8 | ALUMINUM |
| 4200-S3     | 5/16-18 X 3/8 | STEEL    |
| 4200-A5     | 3/8-16 X 9/16 | ALUMINUM |
| 4200-S5     | 3/8-16 X 9/16 | STEEL    |
| 4200-A6     | 1/2-13 X 5/8  | ALUMINUM |
| 4200-S6     | 1/2-13 X 5/8  | STEEL    |

**METRIC THREAD STYLES**

|             |                   |          |
|-------------|-------------------|----------|
| 4200-A3/M8  | M8 X 1.25 X 9.5   | ALUMINUM |
| 4200-S3/M8  | M8 X 1.25 X 9.5   | STEEL    |
| 4200-A5/M10 | M10 X 1.50 X 14.2 | ALUMINUM |
| 4200-S5/M10 | M10 X 1.50 X 14.2 | STEEL    |
| 4200-A6/M10 | M12 X 1.75 X 15.8 | ALUMINUM |
| 4200-S6/M10 | M12 X 1.75 X 15.8 | STEEL    |

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL  
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 06-AUG-2008



**MAR-BAL, Incorporated**  
5400 Reserve Way  
Dublin, VA 24084  
www.mar-bal.com

|   |   |
|---|---|
| TITLE<br><b>4000 SERIES OCTAGON INSULATOR</b> |   |
| PART NUMBER:<br><b>4200-XX</b>                | SUGGESTED INDOOR RATING:<br><b>2.5 kV</b> |
| SHEET 1 OF 1                                  | SCALE 1.000                               |