



OVER SURFACE SPACING
(CREEP DISTANCE) = 3.188"

AVAILABLE THREADS

UNC THREAD STYLES

PART NUMBER	INSERT SIZE	MATERIAL
5263-A6	1/2-13 X 5/8	ALUMINUM
5263-S6	1/2-13 X 5/8	STEEL
5263-A8	5/8-11 X 3/4	ALUMINUM
5263-S8	5/8-11 X 3/4	STEEL

METRIC THREAD STYLES

5263-A6/M12	M12 X 1.75 X 15.8	ALUMINUM
5263-S6/M12	M12 X 1.75 X 15.8	STEEL
5263-A8/M16	M16 X 2.00 X 19.0	ALUMINUM
5263-S8/M16	M16 X 2.00 X 19.0	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 04-AUG-2008



MAR-BAL, Incorporated
5400 Reserve Way
Dublin, VA 24084
www.mar-bal.com

TITLE 5000 SERIES OCTAGON INSULATOR	
PART NUMBER: 5263-XX	SUGGESTED INDOOR RATING: 3.4 kV
SHEET 1 OF 1	SCALE 1.000