



OVER SURFACE SPACING
(CREEP DISTANCE) = 4.25"

B

B

A

A

AVAILABLE THREADS		
UNC THREAD STYLES		
PART NUMBER	INSERT SIZE	MATERIAL
5375-A5	3/8-16 X 9/16	ALUMINUM
5375-S8	5/8-11 X 3/4	STEEL
5375-S10	3/8-16 X 5/8	STEEL
METRIC THREAD STYLES		
5375-A5/M10	M10 X 1.50 X 14.2	ALUMINUM
5375-S8/M16	M16 X 2.00 X 19.0	STEEL
5375-S10/M10	M10 X 1.50 X 14.2	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 04-AUG-2008



MAR-BAL, Incorporated
5400 Reserve Way
Dublin, VA 24084
www.mar-bal.com

TITLE	
5000 SERIES OCTAGON INSULATOR	
PART NUMBER:	SUGGESTED INDOOR RATING:
5375-XX	5.0 kV
SHEET 1 OF 1	SCALE 1.000