



OVER SURFACE SPACING
(CREEP DISTANCE) = 2.125"

AVAILABLE THREADS

UNC THREAD STYLES

PART NUMBER	INSERT SIZE	MATERIAL
R4200-A3	5/16-18 X 3/8	ALUMINUM
R4200-A4	3/8-16 X 3/8	ALUMINUM
R4200-S4	3/8-16 X 3/8	STEEL
R4200-A5	3/8-16 X 9/16	ALUMINUM
R4200-S5	3/8-16 X 9/16	STEEL

METRIC THREAD STYLES

R4200-A3/M8	M8 X 1.25 X 9.5	ALUMINUM
R4200-A4/M10	M10 X 1.50 X 9.5	ALUMINUM
R4200-S4/M10	M10 X 1.50 X 9.5	STEEL
R4200-A5/M10	M10 X 1.50 X 14.2	ALUMINUM
R4200-S5/M10	M10 X 1.50 X 14.2	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 06-AUG-2008



MAR-BAL, Incorporated
5400 Reserve Way
Dublin, VA 24084
www.mar-bal.com

TITLE	
4000 SERIES ROUND INSULATORS	
PART NUMBER:	SUGGESTED INDOOR RATING:
R4200-XX	2.5 kV
DATE: 06-AUG-2008	SCALE 1.000