



TENSILE STRENGTH:.....2,500 LBS
 CANTILEVER STRENGTH:3,000 LBS
 COMPRESSIVE STRENGTH:.....25,000 LBS
 TORQUE STRENGTH: 35 FT. LBS
 ARC RESISTANCE:.....180 SEC
 UL 94 FLAME RESISTANCE: 94 V-0
 CREEP DISTANCE:5/16" + DIM "A"
 TRACK RESISTANCE:.....600 MINUTES

HEIGHT "A"	THREADS	PART NUMBER	"B" (reference)	VOLTAGE
2.50 [63.5]	3/8 - 16	1872-1A	0.25"	3200
	1/2 - 13	1872-2A		
2.625" [66.7]	5/8 - 11	1872-3F	0.38"	3400
2.75 [69.9]	3/8 - 16	1872-1B	0.50"	3600
	1/2 - 13	1872-2B		
3.00 [76.2]	3/8 - 16	1872-1C	0.75"	4100
	1/2 - 13	1872-2C		
3.25 [82.6]	3/8 - 16	1872-1D	1.00"	4500
	1/2 - 13	1872-2D		
3.50 [88.9]	3/8 - 16	1872-1E	1.25"	5000
	1/2 - 13	1872-2E		
	5/8 - 11	1872-3E		

CONFIDENTIAL
 This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.



MAR-BAL, Incorporated
 5400 Reserve Way
 Dublin, VA 24084
 www.mar-bal.com

TITLE GLASTIC SERIES INSULATORS	
PART NUMBER: 1872-XX	SUGGESTED INDOOR RATING: SEE CHART
DATE: SHEET 1 OF 1	SCALE 1.000