



QMFZ2.E80533 - Plastics - Component

Plastics - Component

See General Information for Plastics - Component

MAR-BAL INC

787 RENAISSANCE PARKWAY
PAINESVILLE, OH 44077 USA

E80533

Material Dsg	Color	Min. Thk mm	Flame Class	H H		Elec	RTI		H D		
				W I	A I		Mech Imp	Str	V R	4 5	C T I
Unsaturated Polyester (UP), glass reinforced, furnished as bulk.											
MB1000-15	ALL	1.5	HB	1	0	130	130	130	0	4	1
		3.0	-	-	-	130	130	130			
MB2000-10	ALL	1.5	V-0	0	0	130	130	130	0	3	1
		3.0	-	-	-	130	130	130			
MB2000-10CG	VT	1.7	V-0	-	-	130	130	130	-	-	-
		3.0	V-0	-	-	130	130	130			
MB2000-10DB	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	-	-	-	130	130	130			
		6.0	-	-	-	130	130	130			
MB2000-10DW	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	-	-	-	130	130	130			
		6.0	-	-	-	130	130	130			
MB2000-10PS	ALL	1.5	V-0	0	0	130	130	130	0	3	0
		3.0	-	0	0	130	130	130			
MB2000-10TG	WT	1.5	V-0	-	-	130	130	130	-	-	-
		3.0	-	-	-	130	130	130			
MB2000-15(a), MB2000-15-AR(a)	More	1.5	V-0	0	0	130	130	130	0	3	0

Cookies on UL
We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. Learn More

Cookie Settings

✓ Accept

		3.0	-	-	-	130	130	130			
MB2000-15LS	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	V-0	0	0	130	130	130			
MB2000-15SF	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	V-0	0	0	130	130	130			
MB2000-20	ALL	1.5	V-0	0	0	130	130	130	0	3	0
		3.0	V-0	0	0	130	130	130			
MB2000-20A	ALL	1.5	V-1	1	0	130	130	130	0	4	0
		3.0	-	-	-	130	130	130			
MB2000-25	ALL	1.5	V-0	0	0	130	130	130	0	2	1
		3.0	-	-	-	130	130	130			
MB2000-25EK	ALL	1.5	V-0	1	0	130	130	130	0	4	0
		3.0	V-0	0	0	130	130	130			
MB2000-5	ALL	1.5	V-0	0	0	130	130	130	0	3	1
		3.0	-	-	-	130	130	130			
MB3000-15	ALL	2.3	V-0	-	-	105	130	130	-	-	-
MB4000@	ALL	1.65	V-0, 5VA	1	0	130	130	130	0	3	0
		1.65	RP15	-	-	130	130	130			
		3.0	V-0, 5VA	0	0	130	130	130			
		3.0	RP15	-	-	130	130	130			
MB5500	ALL	1.3	V-0	0	0	160	160	170	0	4	0
		2.3	V-0, 5VA	0	0	160	160	170			
		3.0	V-0, 5VA	-	-	160	160	170			
MB7000	RD, BK	4.0	V-1	-	-	180	170	200	-	-	-
	ALL	6.0	V-0	-	-	180	170	200			
MB9000-20	ALL	1.5	V-0	0	0	130	130	130	0	4	0
		3.0	V-0	-	-	130	130	130			
<p>Unsaturated Polyester (UP), furnished as bulk.</p>											
MB1000-PC	BK	1.5	HB	0	0	130	130	130			
		3.0	HB	0	0	130	130	130			
MB3000-15-NV (S)	ALL	1.5	V-0, 5VA	0	0	130	130	130	0	4	0

Cookies on UL

We use cookies to personalize

content and ads, to provide social

media features and to analyze our

traffic. We also share information

about your use of our site with our

social media, advertising and

analytics partners. [Learn More](#)

Cookie Settings

✓ Accept

		3.0	V-0, 5VA	0	0	130	130	130			
MB-3000-20-NY	ALL	1.5	V-0, 5VA	0	0	130	130	130	0	4	0
		3.0	V-0, 5VA	0	0	130	130	130			
MB1000-10	ALL	1.5	HB	2	0	130	130	130	0	4	0
		3.0	HB	1	0	130	130	130			

(a) - Material has been subjected to inclined plane tracking test in accordance with ASTM D-2303, no tracking was observed at 1.5kV at less than 60 s.

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

@ - Material has been subjected to inclined plane tracking test in accordance with ASTM D-2303, tracking less than 1 inch after 1500 minutes at 2500 volts.

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2020-05-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[> Cookie Settings](#)

✓ Accept